# **CORE LINEPIPE**



### Head Office

910, 736-8th Ave SW Calgary, AB. T2P 1H4 Phone: (587) 333-6685

### **Production Plant**

10 McCool Crescent Crossfi eld, AB. TOM 0S0

## **CORELinepipe.com**

### Manufacturers of pre-lined and pre-coated steel pipelines. WHAT WE DO

Supply a proprietary linepipe system that eliminates internal corrosion, provides dual containment and has zero fugitive emmissions.

- X52 steel linepipe with factory installed PE4710 liner
- Internal liner joined using premium electrofusion couplings. >40,000 installed
- Proprietary mechanical joining system (ClickWeld<sup>TM</sup>) to connect steel
- · Integrated field services, project support and pipeline design

### **PRODUCT PERFORMANCE**

• Liner is installed in a factory environment using tight tolerances and stringent QC programs

• CORE Liner is designed to eliminate manpower, equipment and human error. The process is consistent, repeatable and controlled

• CORE Linepipe uses premium materials customized to meet the requirements of service

• Consultation on design, engineering support (applications engineer), and a range of material options to meet demand

- Preventative leak detection is available in combination with dual containment
- 6.5 years of operating history with ZERO in service failures
- 25 year minimum design life, made in Canada

#### **CORE EFFICIENCY AND COST CERTAINTY**

- Eliminating logistical challenges of installation
- Reduced freight
- One hydrotest
- No pulling liner in ditch/bell holes
- Reduced workspace requirements
- Less vulnerable to weather delays
- Very few bid clarifi cations
- - No welding
  - No separate liner crew
  - No bell holes

7-10 (min) / joint

- 3000 3500 (ft) / day
- 4 person crew
- Reduced footprint and manpower

### BY DESIGN WE ARE DRIVING TO COST CERTAINTY.

\*CORE Liner<sup>™</sup>

Shawn Tyner

c: 970.623.1667

**\*CORE ClickWeld**<sup>™</sup>

## **\*CORE Service**<sup>™</sup>

### For more information contact:

Aethan Sakell VP of Business Development c: 403.589.3012 e: ASakell@corelinepipe.com

e: STyner@corelinepipe.com

Dane Lee Broussard **Executive Director** c: 713.444.0797 e: DBroussard@corelinepipe.com

\*CORE Coat<sup>™</sup>

Rusty Padgett Construction Superintendent/Field Sales Technical Sales Representative c: 970.210.0070 e: RPadgett@corelinepipe.com

**CORE LINEPIPE** 




## **CORE LINEPIPE**



## engineered marvels that change everything

Eliminates traditional field welding drastically reducing pipeline costs.

Expect:



Construction time is <sup>1</sup>/<sub>2</sub> of conventional slip liner, reducing pipeline costs.



### Head Office

910, 736- 8th Ave SW Calgary, AB. T2P 1H4 Phone: (587) 333-6685

### **Production Plant**

10 McCool Crescent Crossfield, AB. T0M 0S0

**CORELinepipe.com** 

### Manufacturers of pre-lined and pre-coated steel pipelines.

**APPLICATION ENVELOPE** 



PARAMETER	SPECIFICATION
Pressure	Up to 1500 ANSI/ 3500 psi/ 22,400 kPa
Temperature	$140^oF$ / $60^oC$ (Oil Emulsion) $180^oF$ / $80^oC$ (Water Service)

Product Data is subject to change without notice. Patent Pending. \*Consult your CORE Linepipe representative for more information.

### **PRODUCT SPECIFICATIONS**

PRODUCT	SPECIFICATION
Steel pipe	ERW, CSA Z245.1 GR. 359 CAT II / API 5L X52
Thermoplastic liner	Bi-modal HDPE 4710, API 15LE
External Coating	3-Layer FBE with Polyethylene
Pressure	Up to 22,400 kPa / 3,500 psi
Temperature	Up to 82°C / 180°F (Application dependent)
Flow Coefficient	Hazen & Williams 150 / Darcy Weisbach = 0.000005 ft or 0.0015mm / Manning 0.009

\*Other material options are available by special order. (Non-Permeating Liner)

Product	NPS	Nominal steel outside diameter		Steel wall thickness		Liner inside diameter		Liner wall thickness		ClickWeld <sup>™</sup> coupling outside diameter		Weight	
		mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	kg/ m	lbs/ ft
CL 440	4"	114.3	4.50	4.00	0.157	94.7	3.73	5.80	0.23	152.0	5.98	13.0	9.0
CL 648	6"	168.3	6.63	4.80	0.189	146.0	5.75	6.30	0.25	210.0	8.25	24.0	16.0
CL 671	6"	168.3	6.63	7.10	0.280	141.0	5.58	6.10	0.24	220.0	8.66	34.0	23.0
CL 856	8"	219.1	8.63	5.60	0.220	191.0	7.52	8.30	0.33	273.0	10.75	38.0	25.0

\*Other material options are available by special order.



We are one part engineering excellence and one part passion. Using this formula, nature and history are full of solutions that have changed everything.



**CORE LINEPIPE**